

## Quad Multi Module



### Introduction

The E-Plex 325QMM series contains four channels up to five amps each. This allows the control of up to four different devices. These channels can be combined to handle larger amperage requirements if desired. The module also incorporates thermal, short circuit and programmable overload protection. With the ability to also include up to two dimmers, the module is capable of controlling lighting circuits without requiring additional modules.

**Note:** External surge suppression is required when the module battery supply cable is longer than 50'.

### Key Features

- 4 channel outputs capable to 5 amps each (20 amps total).
- 2 channels with PWM dimming capabilities.
- Thermal and overload protection.
- Unused outputs can be used as inputs.
- Programmable overload protection via E-Logic.
- LEN value 3.



52 – 54 Riverside, Sir Thomas Longley Road, Medway City Estate, Rochester, Kent ME2 4DP  
tel: +44 (0)1634 711622 fax: +44 (0)1634 290773

email: [sales@e-plex.co](mailto:sales@e-plex.co)  
web: [www.e-plex.co](http://www.e-plex.co)

Important Notice: E-Plex Ltd. (E-Plex) reserves the right to make changes to or discontinue any product or service identified in this publication without notice. E-Plex advises its customers to obtain the latest version of the relevant information to verify, before placing any orders, that the information being relied upon is current. E-Plex assumes no responsibility for infringement of patents or rights of others based on E-Plex applications assistance or product specifications since E-Plex does not possess full access concerning the use or application of customers' products. E-Plex also assumes no responsibility for customers' product designs.